

# 1, 2 & 3 CHANNEL RECEIVERS



## Specification:

Encryption:	Code-Hopping
Range:	150m (Open air)
Frequency:	403MHz
Memory Capacity:-	
RX1-150	80 Remotes
RX2-150	40 Remotes
RX3-150	32 Remotes
Voltage Range:	9.8V to 26V AC/DC
Current draw:	15mA
Dimensions (lxbxh):	187 x 104 x 67mm
Weight RX1-150:	50grams
Weight RX2-150:	75grams
Weight RX3-150:	85grams
Operating Temp:	-5°C to 60°C
Warranty:	24 Months
Release Date:	June 2009

## Order Code

1 Channel Receiver	RX1-150
2 Channel Receiver	RX2-150
3 Channel Receiver	RX3-150
1 Ch BUSLINE Receiver	BUSRX
BUSLINE Receiver KIT	BUSRX_KIT

## Features

Code-Hopping Encryption

Latch or Momentary

Selectable Momentary times:

1 Sec; 3Sec; 1min; 3min

Buzzer tone

Crystal Controlled +/- 100KHz

Frequencies: 403MHz / 433MHz

12 - 24V AC/DC input

## Applications

Gate & Garage Door Access Control

Panic Activations

Arming / Disarming Alarm systems

Switching On / Off lights

Switching On / Off Generators



New Erase  
Function